

Technical Data - Europe.

BMW 5 Series Touring (E61) - ACEA.

| | 523i Touring | 523i Touring | 525i Touring | 525i Touring | 530i Touring | 530i Touring | 550i Touring | 550i Touring | M5 Touring |
|--|---------------------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|
| Engine platform | N53B25U0 | N53B25U0 | N53B30U0 | N53B25U0 | N53B30U0 | N53B30U0 | N62B48O1 | N62B48O1 | S85B50 |
| Transmission | M6 | A6 | M6 | A6 | M6 | A6 | M6 | A6 | M6 |
| No of doors / seats | - / 5 | - / 5 | - / 5 | - / 5 | - / 5 | - / 5 | - / 5 | - / 5 | - / 5 |
| Vehicle length / width / height -unloaded- | mm 4843 / 1846 / 1491 | mm 4843 / 1846 / 1491 | mm 4843 / 1846 / 1491 | mm 4843 / 1846 / 1491 | mm 4843 / 1846 / 1491 | mm 4843 / 1846 / 1491 | mm 4843 / 1846 / 1491 | mm 4843 / 1846 / 1491 | mm 4855 / 1846 / 1512 |
| Weelbase / Turning cicle | mm / m 2886 / 11,4 | mm / m 2886 / 11,4 | mm / m 2886 / 11,4 | mm / m 2886 / 11,4 | mm / m 2886 / 11,4 | mm / m 2886 / 11,4 | mm / m 2886 / 11,4 | mm / m 2886 / 11,4 | mm / m 2880 / 12,4 |
| Track front / rear | mm 1558 / 1581 | mm 1558 / 1581 | mm 1558 / 1581 | mm 1558 / 1581 | mm 1558 / 1581 | mm 1558 / 1581 | mm 1558 / 1581 | mm 1558 / 1581 | mm 1590 / 1588 |
| Overhang rear | mm 1105 | mm 1105 | mm 1105 | mm 1105 | mm 1105 | mm 1105 | mm 1105 | mm 1105 | mm 1111 |
| Ground clearance -empty- | mm 143 | mm 143 | mm 143 | mm 143 | mm 143 | mm 143 | mm 143 | mm 143 | mm - |
| Shoulder width front / rear | mm 1456 / 1454 | mm 1456 / 1454 | mm 1456 / 1454 | mm 1456 / 1454 | mm 1456 / 1454 | mm 1456 / 1454 | mm 1456 / 1454 | mm 1456 / 1454 | mm 1456 / 1452 |
| Elbow width front / rear | mm 1484 / 1496 | mm 1484 / 1496 | mm 1484 / 1496 | mm 1484 / 1496 | mm 1484 / 1496 | mm 1484 / 1496 | mm 1484 / 1496 | mm 1484 / 1496 | mm 1484 / 1496 |
| Eff. head room front / rear | mm 992 / 994 | mm 992 / 994 | mm 992 / 994 | mm 992 / 994 | mm 992 / 994 | mm 992 / 994 | mm 992 / 994 | mm 992 / 994 | mm 992 / 994 |
| Luggage capacity | m³ 0,500-1,650* | m³ 0,500-1,650* | m³ 0,500-1,650* | m³ 0,500-1,650* | m³ 0,500-1,650* | m³ 0,500-1,650* | m³ 0,500-1,650* | m³ 0,500-1,650* | m³ 0,500-1,650* |
| Fuel tank capacity | ltr 70 | ltr 70 | ltr 70 | ltr 70 | ltr 70 | ltr 70 | ltr 70 | ltr 70 | ltr 70 |
| Curb weight -acc DIN- | kg 1590 / 1665 | kg 1620 / 1695 | kg 1605 / 1680 | kg 1630 / 1705 | kg 1620 / 1695 | kg 1630 / 1705 | kg 1760 / 1835 | kg 1760 / 1835 | kg 1880 / 1955 |
| Axle load ratio -unloaded DIN- | % 53,1 | % 52,5 | % 53,0 | % 52,5 | % 52,8 | % 52,5 | % 51,7 | % 51,7 | % 50,5 |
| Gross vehicle weight / Payload | kg 2190 / 600 | kg 2220 / 600 | kg 2205 / 600 | kg 2230 / 600 | kg 2220 / 600 | kg 2230 / 600 | kg 2320 / 560 | kg 2320 / 560 | kg 2415 / - |
| Axle load limit front / rear | kg 980 / 1290 | kg 980 / 1290 | kg 980 / 1300 | kg 980 / 1300 | kg 980 / 1300 | kg 980 / 1300 | kg 1070 / 1300 | kg 1070 / 1300 | kg 1090 / 1360 |
| Trailer load braked -12% / 8%/- | kg 1800 / 1800 | kg 1800 / 1800 | kg 1800 / 2000 | kg 2000 / 2000 | kg 2000 / 2000 | kg 2000 / 2000 | kg 2000 / 2000 | kg 2000 / 2000 | kg 1800 / 1800 |
| Trailer load unbraked / roof load | kg 750 / 100 | kg 750 / 100 | kg 750 / 100 | kg 750 / 100 | kg 750 / 100 | kg 750 / 100 | kg 750 / 100 | kg 750 / 100 | kg 750 / 100 |
| Engine type / cylinder / valves p cyl | - In line / 6 / 4 | - In line / 6 / 4 | - In line / 6 / 4 | - In line / 6 / 4 | - In line / 6 / 4 | - In line / 6 / 4 | - In line / 6 / 4 | - In line / 6 / 4 | - V 90 / 10 / 4 |
| Fuel management | - MSD80 | - MSD80 | - MSD80 | - MSD80 | - MSD80 | - MSD80 | - ME9,2,3 | - ME9,2,3 | - BMW MS S65 |
| Effective displacement | cm³ 2497 | cm³ 2497 | cm³ 2996 | cm³ 2996 | cm³ 2996 | cm³ 2996 | cm³ 4799 | cm³ 4799 | cm³ 4999 |
| Stroke / Bore | mm 78,8 / 82 | mm 78,8 / 82 | mm 88 / 85 | mm 88 / 85 | mm 88 / 85 | mm 88 / 85 | mm 88,3 / 93 | mm 88,3 / 93 | mm 75,2 / 92 |
| Nom power output / Engine speed | kW(hp) / 1/min 140 (190) / 6300 | kW(hp) / 1/min 140 (190) / 6300 | kW(hp) / 1/min 160 (218) / 6100 | kW(hp) / 1/min 160 (218) / 6100 | kW(hp) / 1/min 200 (272) / 6700 | kW(hp) / 1/min 200 (272) / 6700 | kW(hp) / 1/min 270 (367) / 6300 | kW(hp) / 1/min 270 (367) / 6300 | kW(hp) / 1/min 373 (507) / 7750 |
| Max torque / Engine speed | Nm / 1/min 235 / 3500 | Nm / 1/min 235 / 3500 | Nm / 1/min 270 / 2400 | Nm / 1/min 270 / 2400 | Nm / 1/min 320 / 2750 | Nm / 1/min 320 / 2750 | Nm / 1/min 490 / 3400 | Nm / 1/min 490 / 3400 | Nm / 1/min 520 / 6100 |
| RPM at max torque -range- | 1/min see "Tor./Engine speed" | 1/min see "Tor./Engine speed" | 1/min 2400-4200 | 1/min 2400-4200 | 1/min 2750-3000 | 1/min 2750-3000 | 1/min see "Tor./Engine speed" | 1/min see "Tor./Engine speed" | 1/min see "Tor./Engine speed" |
| Compression ratio / Fuel type | - 12 / ROZ91-98 | - 12 / ROZ91-98 | - 12 / ROZ91-98 | - 12 / ROZ91-98 | - 12 / ROZ91-98 | - 12 / ROZ91-98 | - 10,5 / ROZ91-98 | - 10,5 / ROZ91-98 | - 12 / ROZ95-98 |
| Exhaust emissions classification | - EU4 | - EU4 | - EU4 | - EU4 | - EU4 | - EU4 | - EU4 | - EU4 | - EU4 |
| Codification of reference gearbox | - GETRAG I | - ZF 6HP19 Tü | - GETRAG I | - ZF 6HP19 Tü | - GETRAG I | - ZF 6HP19 Tü | - ZF G | - ZF 6HP26 Tü | - SMG III 247 |
| Gear ratio 1st/2nd/3rd | - 4,323 / 2,456 / 1,659 | - 4,171 / 2,34 / 1,521 | - 4,323 / 2,456 / 1,659 | - 4,171 / 2,34 / 1,521 | - 4,35 / 2,496 / 1,665 | - 4,171 / 2,34 / 1,521 | - 4,055 / 2,396 / 1,582 | - 4,171 / 2,34 / 1,521 | - 3,985 / 2,652 / 1,806 |
| Gear ratio 4th/5th/6th/7th | - 1,23 / 1 / 0,848 / - | - 1,143 / 0,867 / 0,691 / - | - 1,23 / 1 / 0,848 / - | - 1,143 / 0,867 / 0,691 / - | - 1,23 / 1 / 0,851 / - | - 1,143 / 0,867 / 0,691 / - | - 1,192 / 1 / 0,872 / - | - 1,143 / 0,867 / 0,691 / - | - 1,392 / 1,159 / 0,833 / - |
| Reverse ratio | - 3,938 | - 3,403 | - 3,938 | - 3,403 | - 3,926 | - 3,403 | - 3,677 | - 3,403 | - 3,985 |
| Final drive ratio | - 3,38 | - 3,91 | - 3,23 | - 3,64 | - 3,23 | - 3,73 | - 2,93 | - 3,38 | - 3,62 |
| Steering type / ratio | - Rack-and-pinion / 13,7 | - Rack-and-pinion / 13,7 | - Rack-and-pinion / 13,7 | - Rack-and-pinion / 13,7 | - Rack-and-pinion / 13,7 | - Rack-and-pinion / 13,7 | - Rack-and-pinion / 13,7 | - Rack-and-pinion / 13,7 | - Rack-and-pinion / 12,4 |
| Brake front / diameter | -/mm Ventilated Disc / 324 | -/mm Ventilated Disc / 324 | -/mm Ventilated Disc / 324 | -/mm Ventilated Disc / 324 | -/mm Ventilated Disc / 348 | -/mm Ventilated Disc / 348 | -/mm Ventilated Disc / 348 | -/mm Ventilated Disc / 348 | -/mm Ventilated Disc / 374 |
| Brake rear / diameter | -/mm Ventilated Disc / 320 | -/mm Ventilated Disc / 320 | -/mm Ventilated Disc / 320 | -/mm Ventilated Disc / 320 | -/mm Ventilated Disc / 345 | -/mm Ventilated Disc / 345 | -/mm Ventilated Disc / 345 | -/mm Ventilated Disc / 345 | -/mm Ventilated Disc / 370 |
| Drag Cd / A / Cd x A | - / m² / m² 0,29 / 2,26 / 0,66 | - / m² / m² 0,28 / 2,26 / 0,63 | - / m² / m² 0,29 / 2,26 / 0,66 | - / m² / m² 0,28 / 2,26 / 0,63 | - / m² / m² 0,29 / 2,26 / 0,66 | - / m² / m² 0,29 / 2,26 / 0,66 | - / m² / m² 0,29 / 2,26 / 0,66 | - / m² / m² 0,29 / 2,26 / 0,66 | - / m² / m² 0,32 / 2,26 / 0,72 |
| Top speed | km/h 230 | km/h 229 | km/h 243 | km/h 241 | km/h 250 | km/h 250 | km/h 250 | km/h 250 | km/h 250 |
| Acceleration 0-100 Km/h | s 8,5 | s 9,1 | s 7,4 | s 7,9 | s 6,5 | s 6,8 | s 5,3 | s 5,4 | s 4,8 |
| Acceleration 0-1000 m | s 29,3 | s 29,7 | s 27,7 | s 28,2 | s 26,3 | s 26,5 | s 24,3 | s 24,5 | s 22,9 |
| Accel 80-120 Km/h 4/5 Gear | s 9,2 / - / - | s - / - / - | s 8,1 / - / - | s - / - / - | s 7 / - / - | s - / - / - | s 5,3 / - / - | s - / - / - | s - / - / - |
| Weight ratio | kg/kW 11,4 | kg/kW 11,6 | kg/kW 10,0 | kg/kW 10,2 | kg/kW 8,1 | kg/kW 8,2 | kg/kW 6,5 | kg/kW 6,5 | kg/kW 5,0 |
| Output per litre | kW/ltr 56,1 | kW/ltr 56,1 | kW/ltr 53,4 | kW/ltr 53,4 | kW/ltr 66,8 | kW/ltr 66,8 | kW/ltr 56,3 | kW/ltr 56,3 | kW/ltr 74,6 |
| Fuel consumption -EU urban- | ltr/100km 10,6 | ltr/100km 10,6 | ltr/100km 10,8 | ltr/100km 10,7 | ltr/100km 11,1 | ltr/100km 11,0 | ltr/100km 17,0 | ltr/100km 16,1 | ltr/100km 22,4 |
| Fuel consumption -EU extra-urban- | ltr/100km 6,0 | ltr/100km 6,0 | ltr/100km 5,9 | ltr/100km 6,0 | ltr/100km 5,8 | ltr/100km 5,8 | ltr/100km 7,8 | ltr/100km 7,5 | ltr/100km 10,6 |
| Fuel consumption KV01 / Range | ltr/100km / km 7,7 / 905 | ltr/100km / km 7,7 / 905 | ltr/100km / km 7,7 / 905 | ltr/100km / km 7,7 / 905 | ltr/100km / km 7,9 / 885 | ltr/100km / km 7,7 / 905 | ltr/100km / km 11,2 / 625 | ltr/100km / km 10,7 / 650 | ltr/100km / km 15 / 465 |
| CO2-emission -EU- | g/km 183 | g/km 184 | g/km 183 | g/km 184 | g/km 187 | g/km 184 | g/km 267 | g/km 254 | g/km 361 |
| Tyre type -front- | - 225/55 R16 95W | - 225/55 R16 95W | - 225/55 R16 95W | - 225/55 R16 95W | - 225/50 R17 94Y | - 225/50 R17 94Y | - 225/50 R17 94Y | - 225/50 R17 94Y | - 255/40 ZR19 |
| Tyre type -rear- | - 225/55 R16 95W | - 225/55 R16 95W | - 225/55 R16 95W | - 225/55 R16 95W | - 225/50 R17 94Y | - 225/50 R17 94Y | - 225/50 R17 94Y | - 225/50 R17 94Y | - 275/35 ZR19 |
| Front rim | - 7J x 16 Light alloy | - 7J x 16 Light alloy | - 7J x 16 Light alloy | - 7J x 16 Light alloy | - 7,5J x 17 Light alloy | - 7,5J x 17 Light alloy | - 8J x 17 Light alloy | - 8J x 17 Light alloy | - 8,5J x 19L Light alloy |
| Rear rim | - 7J x 16 Light alloy | - 7J x 16 Light alloy | - 7J x 16 Light alloy | - 7J x 16 Light alloy | - 7,5J x 17 Light alloy | - 7,5J x 17 Light alloy | - 8J x 17 Light alloy | - 8J x 17 Light alloy | - 9,0J x 19 Light alloy |
| Wheel offset -front/rear- | mm 20 / 20 | mm 20 / 20 | mm 43 / 43 | mm 20 / 20 | mm 20 / 20 | mm 20 / 20 | mm 20 / 20 | mm 20 / 20 | mm - / - |
| Radiator incl. heater / Engine oil exchange quantity | ltr 10 / 6,5 | ltr 10 / 6,5 | ltr 10 / 6,5 | ltr 10 / 6,5 | ltr 10 / 6,5 | ltr 10 / 6,5 | ltr 13,8 / 8 | ltr 13,8 / 8 | ltr 15 / 9,3 |
| Transmission fluid -exchange quantity- | ltr Permanent filling | ltr Permanent filling | ltr Permanent filling | ltr Permanent filling | ltr Permanent filling | ltr Permanent filling | ltr Permanent filling | ltr Permanent filling | ltr Exch. quantity (2,4) |
| Battery capacity / installed position | Ah/- 90 / Luggage comp. | Ah/- 90 / Luggage comp. | Ah/- 90 / Luggage comp. | Ah/- 90 / Luggage comp. | Ah/- 90 / Luggage comp. | Ah/- 90 / Luggage comp. | Ah/- 90 / Luggage comp. | Ah/- 90 / Luggage comp. | Ah/- 90 / Luggage comp. |
| Alternator output rating | A/W 155 / 2170 | A/W 155 / 2170 | A/W 155 / 2170 | A/W 155 / 2170 | A/W 155 / 2170 | A/W 155 / 2170 | A/W 180 / 2520 | A/W 180 / 2520 | A/W 170 / 2380 |

Technical Data - Europe.

BMW 5 Series Touring (E61) - ACEA.

* with runflat tyres

| | 525xi Touring | 525xi Touring | 530xi Touring | 530xi Touring | 530xd Touring | 530xd Touring |
|--|--------------------------------|---------------------------|-------------------------|---------------------------|-------------------------|---------------------------|
| Engine platform | N53B30U0 | N53B30U0 | N53B30O0 | N53B30O0 | M57D30O0 | M57D30O2 |
| Transmission | M6 | A6 | M6 | A6 | M6 | A6 |
| No of doors / seats | - / 5 | - / 5 | - / 5 | - / 5 | - / 5 | - / 5 |
| Vehicle length / width / height -unloaded- | mm 4843 / 1846 / 1491 | 4843 / 1846 / 1491 | 4843 / 1846 / 1491 | 4843 / 1846 / 1491 | 4843 / 1846 / 1491 | 4843 / 1846 / 1491 |
| Wheelbase / Turning circle | mm / m 2886 / 11,9 | 2886 / 11,9 | 2886 / 11,9 | 2886 / 11,9 | 2886 / 11,9 | 2886 / 11,9 |
| Track front / rear | mm 1558 / 1581 | 1558 / 1581 | 1558 / 1581 | 1558 / 1581 | 1558 / 1581 | 1558 / 1581 |
| Overhang rear | mm 1105 | 1105 | 1105 | 1105 | 1105 | 1105 |
| Ground clearance -empty- | mm 143 | 143 | 143 | 143 | 143 | 143 |
| Shoulder width front / rear | mm 1456 / 1454 | 1456 / 1454 | 1456 / 1454 | 1456 / 1454 | 1456 / 1454 | 1456 / 1454 |
| Elbow width front / rear | mm 1484 / 1496 | 1484 / 1496 | 1484 / 1496 | 1484 / 1496 | 1484 / 1496 | 1484 / 1496 |
| Eff. head room front / rear | mm 992 / 994 | 992 / 994 | 992 / 994 | 992 / 994 | 992 / 994 | 992 / 994 |
| Luggage capacity | m³ 0,500-1,650* | 0,500-1,650* | 0,500-1,650* | 0,500-1,650* | 0,500-1,650* | 0,500-1,650* |
| Fuel tank capacity | ltr 70 | 70 | 70 | 70 | 70 | 70 |
| Curb weight -acc DIN- | kg 1720 / 1795 | 1740 / 1815 | 1725 / 1800 | 1735 / 1810 | 1770 / 1845 | 1780 / 1855 |
| Axle load ratio -unloaded DIN- | % 51,2 | 50,9 | 51,3 | 51,0 | 50,6 | 50,0 |
| Gross vehicle weight / Payload | kg 2320 / 600 | 2340 / 600 | 2325 / 600 | 2335 / 600 | 2350 / 580 | 2360 / 580 |
| Axle load limit front / rear | kg 1050 / 1300 | 1050 / 1300 | 1050 / 1300 | 1050 / 1300 | 1090 / 1300 | 1090 / 1300 |
| Trailer load braked -12% / 8%- | kg 1800 / 2000 | 2000 / 2000 | 2000 / 2000 | 2000 / 2000 | 2000 / 2000 | 2000 / 2000 |
| Trailer load unbraked / roof load | kg 750 / 100 | 750 / 100 | 750 / 100 | 750 / 100 | 750 / 100 | 750 / 100 |
| Engine type / cylinder / valves p cyl | - In line / 6 / 4 | In line / 6 / 4 | In line / 6 / 4 | In line / 6 / 4 | In line / 6 / 4 | In line / 6 / 4 |
| Fuel management | - MSD80 | MSD80 | MSD80 | MSD80 | DDE6,2,6 | DDE6,2,6 |
| Effective displacement | cm³ 2996 | 2996 | 2996 | 2996 | 2993 | 2993 |
| Stroke / Bore | mm 88 / 85 | 88 / 85 | 88 / 85 | 88 / 85 | 90 / 84 | 90 / 84 |
| Nom power output / Engine speed | kW(hp)/ 1/min 160 (218) / 6100 | 160 (218) / 6100 | 200 (272) / 6700 | 200 (272) / 6700 | 173 (235) / 4000 | 173 (235) / 4000 |
| Max torque / Engine speed | Nm / 1/min 270 / 2400 | 270 / 2400 | 320 / 2750 | 320 / 2750 | 500 / 1750 | 500 / 1750 |
| RPM at max torque -range- | 1/min 2400-4200 | 2400-4200 | 2750-3000 | 2750-3000 | 1750-3000 | 1750-3000 |
| Compression ratio / Fuel type | - 12 / ROZ91-98 | 12 / ROZ91-98 | 12 / ROZ91-98 | 12 / ROZ91-98 | 17 / Diesel | 17 / Diesel |
| Exhaust emissions classification | - EU4 | EU4 | EU4 | EU4 | EU4 | EU4 |
| Codification of reference gearbox | - ZF H | ZF 6HP19 Tü | ZF H | ZF 6HP19 Tü | ZF Gweit | ZF 6HP19 Tü |
| Gear ratio 1st/2nd/3rd | - 4,35 / 2,496 / 1,665 | 4,171 / 2,34 / 1,521 | 4,35 / 2,496 / 1,665 | 4,171 / 2,34 / 1,521 | 5,08 / 2,804 / 1,783 | 4,171 / 2,34 / 1,521 |
| Gear ratio 4th/5th/6th/7th | - 1,23 / 1 / 0,851 / - | 1,143 / 0,867 / 0,691 / - | 1,23 / 1 / 0,851 / - | 1,143 / 0,867 / 0,691 / - | 1,26 / 1 / 0,835 / - | 1,143 / 0,867 / 0,691 / - |
| Reverse ratio | - 3,926 | 3,403 | 3,926 | 3,403 | 4,607 | 3,403 |
| Final drive ratio | - 3,23 | 3,91 | 3,38 | 3,73 | 2,65 | 2,65 |
| Steering type / ratio | - Rack-and-pinion / 14,58 | Rack-and-pinion / 14,58 | Rack-and-pinion / 14,58 | Rack-and-pinion / 14,58 | Rack-and-pinion / 14,58 | Rack-and-pinion / 14,58 |
| Brake front / diameter | -/mm Ventilated Disc / 324 | Ventilated Disc / 324 | Ventilated Disc / 324 | Ventilated Disc / 324 | Ventilated Disc / 324 | Ventilated Disc / 324 |
| Brake rear / diameter | -/mm Ventilated Disc / 320 | Ventilated Disc / 320 | Ventilated Disc / 320 | Ventilated Disc / 320 | Ventilated Disc / 320 | Ventilated Disc / 320 |
| Drag Cd / A / Cd x A | - / m² / m² 0,31 / 2,28 / 0,71 | 0,3 / 2,26 / 0,68 | 0,31 / 2,28 / 0,71 | 0,3 / 2,28 / 0,68 | 0,31 / 2,28 / 0,71 | 0,31 / 2,28 / 0,71 |
| Top speed | km/h 233 | 230 | 246 | 244 | 235 | 235 |
| Acceleration 0-100 Km/h | s 8,2 | 8,5 | 6,9 | 7,1 | 6,8 | 7,0 |
| Acceleration 0-1000 m | s 28,3 | 28,5 | 26,9 | 27,1 | 27,3 | 27,5 |
| Accel 80-120 Km/h 4/5 Gear | s 9,2 / - / - | - / - / - | 7,4 / - / - | - / - / - | 5,6 / - / - | - / - / - |
| Weight ratio | kg/kW 10,8 | 10,9 | 8,6 | 8,7 | 10,2 | 10,3 |
| Output per litre | kW/ltr 53,4 | 53,4 | 66,8 | 66,8 | 57,8 | 57,8 |
| Fuel consumption -EU urban- | ltr/100km 11,8 | 11,7 | 12,0 | 12,1 | 9,6 | 9,9 |
| Fuel consumption -EU extra-urban- | ltr/100km 6,4 | 6,5 | 6,4 | 6,3 | 5,8 | 5,6 |
| Fuel consumption KV01 / Range | ltr/100km / km 8,4 / 830 | 8,4 / 830 | 8,5 / 820 | 8,4 / 830 | 7,2 / 970 | 7,2 / 970 |
| CO2-emission -EU- | g/km 201 | 201 | 203 | 201 | 192 | 192 |
| Tyre type -front- | - 225/50 R17 94Y | 225/50 R17 94Y | 225/50 R17 94Y | 225/50 R17 94Y | 225/50 R17 94Y | 225/50 R17 94Y |
| Tyre type -rear- | - 225/50 R17 94Y | 225/50 R17 94Y | 225/50 R17 94Y | 225/50 R17 94Y | 225/50 R17 94Y | 225/50 R17 94Y |
| Front rim | - 7,5J x 17 Light alloy | 7,5J x 17 Light alloy | 7,5J x 17 Light alloy | 7,5J x 17 Light alloy | 7,5J x 17 Light alloy | 7,5J x 17 Light alloy |
| Rear rim | - 7,5J x 17 Light alloy | 7,5J x 17 Light alloy | 7,5J x 17 Light alloy | 7,5J x 17 Light alloy | 7,5J x 17 Light alloy | 7,5J x 17 Light alloy |
| Wheel offset -front/rear- | mm 20 / 20 | 43 / 43 | 43 / 43 | 43 / 43 | 43 / 43 | 43 / 43 |
| Radiator incl. heater / Engine oil exchange quantity | ltr 10 / 6,5 | 10,5 / 6,5 | 10 / 6,5 | 10,5 / 6,5 | 8 / 7,7 | 8,2 / 7,7 |
| Transmission fluid -exchange quantity- | ltr Permanent filling | Permanent filling | Permanent filling | Permanent filling | Permanent filling | Permanent filling |
| Battery capacity / installed position | Ah/- 80 / Luggage comp. | 80 / Luggage comp. | 80 / Luggage comp. | 80 / Luggage comp. | 90 / Luggage comp. | 90 / Luggage comp. |
| Alternator output rating | A/W 155 / 2170 | 155 / 2170 | 155 / 2170 | 155 / 2170 | 180 / 2520 | 180 / 2520 |

* with runflat tyres